



Product	Format	Outputs	Inputs	Optically isolated input(s)	Connectors	DMX512	RDM	Fix mode	Electrical protection	Mains powered	Optically isolated outputs
<b>Rail-Split DMX</b>	DIN Rail	6	1	•	Screw terminals	•			None		
<b>Rail-Split RDM</b>	DIN Rail	6	1	•	Screw terminals	•	•	•	425 VAC		
<b>Rail-Split extreme</b>	DIN Rail	6	1	•	Screw terminals	•	•	•	425 VAC & lightning		
<b>Rail-Split RJ45</b>	DIN Rail	4	1	•	RJ45	•	•	•	425 VAC	•	
<b>rackSplit octo</b>	1U 50mm Skinny Rack	8	1	•	XLR5	•	•	•	Transient protected	•	
<b>versaSplit mono</b>	1U Rack	10	1 (modular)	•	XLR3, XLR5, RJ45	•	•	•	80 VAC	•	
<b>versaSplit duo</b>	1U Rack	8	2 (modular)	•	XLR3, XLR5, RJ45	•	•	•	425 VAC	•	
<b>versaSplit duo extreme</b>	1U Rack	8	2 (modular)	•	XLR3, XLR5, RJ45	•	•	•	425 VAC & lightning	•	
<b>versaSplit iso</b>	1U Rack	10	1 (modular)	•	XLR3, XLR5, RJ45	•	•	•	80 VAC	•	•
<b>versaSplit mini</b>	Case	6	1 (modular)	•	XLR3, XLR5, RJ45	•	•	•	80 VAC	•	
<b>DMX-Buffer</b>	Case	1	1		XLR5, RJ45	•	•		None		
<b>DMX-Clarify</b>	Case	1	1		XLR5, RJ45	•		• (permanent)	None		
<b>DMX-Protect</b> (in-line protection device, not splitter)	Case	1	1		XLR5, RJ45	•	•		425 VAC & lightning	Passive	