



daliPSU quad

Category

- c) DALI

Description

- Four circuit DALI bus power supply

Mechanical


- Mounting: DIN rail (35 mm) or surface
- Material: Polycarbonate Plastic - UL94-V0 rated
- Overall Dimensions: 88mm / 5M (W) x 90mm (H) x 62mm (D)
- Mass: 0.2 kg
- Country of manufacture: UK

Environmental

- Operating temperature: 0°C to 40°C
- Storage temperature: -10°C to +50°C
- Operating relative humidity (max): 80% non-condensing
- IP rating: IP20 indoor use only
- Certification: CE, WEEE, RoHS
- Warranty: 2-year (return to base)

Power & Electrical

- Input voltage: 24 VDC
- Power input/loop connector: 2-pin screw terminal (2 no.)
- Input power (max): 25W
- DC fuse: Internal resettable fuse for control electronics



LED indication

- DALI Activity (per circuit)
- Input supply voltage
- DALI bus voltage

DALI connections

- 2-pin Screw Terminal DALI Input (4 no.)
- 2-pin Screw Terminal DALI Loop (4 no.)

DALI outputs

- Voltage: 16V @ 250mA per circuit (4 no.)
- Current (max): 1A
- Internal resettable fuse: 350 mA per circuit (4 no.)


Ordering information

- Product code: daliPSU quad
- Accessories
 - PSU-24-2-FER
 - Commissioner dali

Artistic Licence




Mounting diagram



Application diagram

The diagram below shows how daliPSU quad could be utilised in a typical application.

A DMXtoDALI quad is controlling a DALI circuit (64 ballasts) on each of its 4 outputs. One common 24V PSU is used to power the DMXtoDALI quad and the daliPSU quad.



The Mould Making Workshop
Soby Mews
Bovey Tracey
TQ13 9JG
United Kingdom

Telephone: +44 (0) 20 8863 4515
Email: sales@ArtisticLicence.com
Service: support@ArtisticLicence.com
Web: www.ArtisticLicence.com

Due to our policy of continuing product improvement specifications are subject to change without notice.

All products are covered from date of purchase by a 2-year return to base warranty.

Artistic Licence

daliPSU quad